



Wide Bull Nose

12'' x 6''



*Discover
The Difference®*

Paver Style	Thk. Cm.	Thk. Inches	Layers Per Cube	Sq. Ft. Per Cube	Pcs. Per Cube Ln. Ft. Per Cube	Weight Per Cube	Bands Per Cube	Sq. Ft. Per Band	Weight Per Band	Pcs. Per Band Ln. Ft. Per Band	Pcs. Per Sq. Ft.	Pcs. Per Linear Ft.
12''x 6'' Bull Nose Approx. Dim. 12''x 6''	6	2 3/8''	4	104	208	2230 Lbs.	4	26	557	52	2	2
					104 LF					26 LF		

Stock Colors: Charcoal, Antique Grey, Butternut, Red Flash, Brown Flash, Hickory & Walnut Blend

Physical Requirements (ASTM C-936)

1. Compressive strength-the average compressive strength shall not be less than 8000 P.S.I.
2. Resistance to Freeze Thaw Cycle-dry weight loss not to be greater than 1% of weight when subjected to 50 cycles of freezing and thawing.
3. Absorption-the average absorption of test samples shall not be greater than 5%.
4. Made according to ASTM C936 Specifications



Concrete Stone & Tile Corp.
23 Ridge Road
Branchville, NJ 07826
(973) 948-7193

CST Montgomery Corp.
43 Leonards Drive
Montgomery, NY 12549
(845) 457-4491

CST Products, LLC
345 Route 130
Pedricktown, NJ 00867
(856) 299-5339